



TUNNEL

TFLEX BASE

ORDERING GUIDE

Sample Configuration:

TFLEXBASE-20L/500mA-NW-5300-C001-V14-GY2- _____ - _____ - _____ - _____

1. Specify **BASE LUMINAIRE**
2. Select **OPTIONS**

****PLEASE FILL IN ALL LIGHT BLUE FIELDS****

JOB NAME / LOCATION _____

FIXTURE TYPE _____

CONFIGURATION _____

LUMINAIRE	LED/mA	LUMENS/WATTAGE (for reference only)	OPTIC	CONFIGURATION	VOLTAGE & EL CLASS	FINISH
TFLEXBASE	20L/500mA	5331lm/32.7W	5300	C001 - CONFIGURATION 1	Standard V14 (277V CL1 (SV)) Optional * V05 (480V CL1 (HV)) ^	GY (RAL7040T GREY)
	20L/670mA	6754lm/44W	5301	C003 - CONFIGURATION 3		GY2 (AKZO900GS GREY)
	20L/700mA	6985lm/45.5W	5302	C009 - CONFIGURATION 9		BK (RAL9011T BLACK)
	40L/350mA	7840lm/42.5W	5303	C012 - CONFIGURATION 12		WH (RAL9016T WHITE)
	40L/500mA	10733lm/64W	5304			BZ (RAL8019T BRONZE)
	40L/630mA	13014lm/80W	5305			
	40L/670mA	13673lm/85W	5306			
	40L/700mA	14159lm/89W	5307			
	60L/350mA	11760lm/63W	5308			
	60L/500mA	15994lm/93W	5355			
	60L/610mA	18816lm/114W	5356			
	60L/700mA	20956lm/130W	5369			
				5370		

OPTIONS (add codes below to end of part number above) *

Electrical Options *

- SF - 10 kV + Fuse Cartridge 10x38mm 6A Type GG500V
- SG - 10 kV + Fuse Cartridge 10x38mm 10A Type GG500V
- S3 - 10 kV + No Fuse
- 7S - 20kV + Fuse Cartridge 10x38mm 6A Class CC ^
- 9S - 20kV + Fuse Cartridge 10x38mm 10A Class CC ^
- 0S - 20KV + 2 Fuses 10x38 CC 6A ^
- 1S - 20KV + 2 Fuses 10x38 CC 10A ^
- SS - 20kV + No Fuse ^

Finish Options *

- RALXXXXM (Other RAL matte)
- RALXXXXB (Other RAL brilliant)
- RALXXXXT (Other RAL textured)
- Counter-Connector Options *
- EI - 1 cable gland
- AC - 2 cable glands
- JJ - QPD 5 Pole (for 1-10V or Dali)
- AM - quick-on connector

Painting Options *

- A5 - ISO 9223 C5/C5X - 3000h salt test - Seafront
- A6 - ISO 9223 C4 - 1500h salt test - SeaSide
- Dimming Options *
- D01 - 0 - 10V
- D02 - DALI
- D03 - Bi-Power 50% (if switched line OFF)
- D15 - Telemangement by 0-10V
- D25 - Fix Current
- Controller Options *
- T1 - Lumgate V3

Fixation Options *

- UD - Universal Fixation Stainless Steel for Wall mounting ^
- UE - Universal Fixation Galvanized Steel for Wall mounting ^
- UF - Universal Fixation Stainless Steel (long type) for Wall mounting
- UG - Universal Fixation Galvanized Steel (long type) for Wall mounting
- UI - Universal Fixation Stainless Steel for Roof mounting ^
- UJ - Universal Fixation Galvanized Steel for Roof mounting ^

NOTES:

Color Temp NW Neutral 4000K, CRI70

* Additional cost may apply.

^ Long lead time (up to 10 weeks production time).

+ Extra long lead time (considered MTM/Custom/Studio Complex).

Preliminary data, date of revision: 07/29/2021

Copyright © Schröder Lighting LLC 2021 - Executive Publisher: Erin Szczepanik. 1750 E Golf Road, Suite 391, Schaumburg, IL 60173. The information, descriptions and illustrations herein are of only an indicative nature. Due to advanced developments, we may be required to alter the characteristics of our products without notice. As these may present different characteristics according to the requirements of individual countries, we invite you to consult us.